

HB19K

Model	HB-19K		
System			
Panel Size	19" LCD		
Resolution	1280 x 1024		
Pixel Pitch (H x V)	0.294 x 0.294		
Contrast Ratio (typ.)	1000:1		
Luminance	300 cd/ m ²		
Aspect Ratio	4:3		
Viewing Angle (CR≥5)	85/85/85/85 deg		
Response Time	Tr=1.2 ms, Tf=3.8 ms		
Video Signal	Composite signal 0.7~1.4Vpp/75 ohm, Y:1Vp-p, C:0.3Vp-p		
Video Color System	NTSC/PAL Auto Scanning		
Scan Frequency	H:30~80KHz, V:50~75Hz		
Operation Interfaces			
Front Panel Controls	Menu/Select (Up, Down), Source, -/Select(Left), +/Select(Right), Power, Power LED, Auto/Exit		
Indicators	LED (Power on: Green→ Standby: Red) OSD (No Signal, Video Loss)		
OSD Control	Brightness, Contrast, Clock, Phase, H.Position, V.Position, Sharpness, Volume, Mute, Color, OSD Time Out, OSD Position, OSD Transparency, Auto Setting, Recall, Aspect Ratio, Source/Input Enable		
OSD Language	English, Japanese, French, Russian, German, Chinese-Traditional, Spanish, Chinese-Simplified, Italian		
Connector			
Input Connector	D-sub x 1 DVI x 1 (optional) Video Input (BNC Jack) x 1 Audio Input (RCA Jack) x2 (L+R 1 set) PC Audio Input (Ø 3.5 Jack) x1 S-Video Input (4-pin Jack) x 1 (optional) Power DC Input x 1		
Output Connector	Video looping Output (BNC Jack) x 1		
Mechanical & Electric Design			
2D comb filter			Yes
De-interlace			Yes
Source Lock			Yes
Video Input Looping Impedance			75 Ω
VESA Mounting			